



US011071455B2

(12) **United States Patent**  
**DeHennis et al.**

(10) **Patent No.:** **US 11,071,455 B2**

(45) **Date of Patent:** **Jul. 27, 2021**

(54) **CONTINUOUS ANALYTE MONITORING SYSTEM**

(71) Applicant: **Senseonics, Incorporated,**  
Germantown, MD (US)

(72) Inventors: **Andrew DeHennis,** Germantown, MD (US); **Barkha Raison,** Germantown, MD (US); **Todd Whitehurst,** Germantown, MD (US)

(73) Assignee: **Senseonics, Incorporated,**  
Germantown, MD (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/810,822**

(22) Filed: **Nov. 13, 2017**

(65) **Prior Publication Data**

US 2018/0125364 A1 May 10, 2018

**Related U.S. Application Data**

(62) Division of application No. 14/580,289, filed on Dec. 23, 2014, now Pat. No. 9,814,389.

(Continued)

(51) **Int. Cl.**

**A61B 5/1455** (2006.01)

**A61B 5/00** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **A61B 5/0022** (2013.01); **A61B 5/002** (2013.01); **A61B 5/1459** (2013.01);

(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,846,188 A \* 12/1998 Palti ..... A61B 5/0059

600/300

6,304,766 B1 \* 10/2001 Colvin, Jr. .... A61B 5/0031

128/903

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 1030590 B1 10/2002

EP 2270481 B1 5/2014

(Continued)

*Primary Examiner* — Eric F Winakur

*Assistant Examiner* — Marjam Fardanesh

(74) *Attorney, Agent, or Firm* — Rothwell, Figg, Ernst & Manbeck, P.C.

(57) **ABSTRACT**

An improved analyte monitoring system having a sensor and a transceiver with improved communication and/or user interface capabilities. The transceiver may communicate with and power the sensor. The transceiver may receive one or more analyte measurements from the sensor and may calculate one or more analyte concentrations based on the received analyte measurements. The transceiver may generate analyte concentration trends, alerts, and/or alarms based on the calculated analyte concentrations. The system may also include a display device, which may be, for example, a smartphone and may be used to display analyte measurements received from the transceiver. The display device may execute a mobile medical application. The system may include a data management system, which may be web-based.

**28 Claims, 16 Drawing Sheets**

